

Herbert Wertheim College of Engineering UNIVERSITY of FLORIDA

Ultra-High Performance Concrete Quality Control Testing

Kyle A. Riding, Chris Ferraro, Trey Hamilton, Joel Harley, Daniel Alabi, Raid Alrashidi, Megan Voss, Rami Zamzami

POWERING THE NEW ENGINEER TO TRANSFORM THE FUTURE

POWERING THE NEW ENGINEER TO TRANSFORM THE FUTURE

Engineering School or Sustainable Infrastructure & Environment

UHPC Applications

UF







Engineering School or Sustainable Infrastructure & Environment

Benefits of UHPC

UF

- Tensile performance can allow you to reduce amount of steel reinforcement
- Increase member length or capacity
- Can optimize geometry for lighter member to reduce shipping costs and crane size
- Reduce cover dimensions?
- Dense and discontinuous microstructure can give very high durability alternative to stainless steel and FRP reinforcement

Engineering School or Sustainable Infrastructure & Environment

Ultra-High Performance Concrete

- ACI 239:
 - Very high strength: \geq 22 ksi
 - Specified durability very low permeability
 - Tensile ductility high volumes of fibers (1 4% by volume)
- PCI:

UF

• Will define very high strength: ≥ 17.4 ksi

Typically has ≥ 2% Steel Fibers for strain-hardening



UF

Engineering School or Sustainable Infrastructure & Environment

Qualification Test: Direct Tension Test







POWERING THE NEW ENGINEER TO TRANSFORM THE FUTURE

d=span depth

Engineering School or Sustainable Infrastructure & Environment

Qualification Test: Flexural Strength-ASTM C1609

• PCI is considering recommending First-peak (first crack) flexural strength f_1 , peak flexural strength, and residual flexural strength at L/150



Engineering School or Sustainable Infrastructure & Environment

What About Quality Control Tensile Testing?

- Many current requirements do not require tensile QC testing
- PCI UHPC materials guide is currently considering requiring ASTM C1609 testing of 3 beams from one batch per day per mix, with an additional 3 beams required if volume exceeds 25 yd³
- Because tensile strength is so integral to performance and in some cases safety, what test should be used at production facilities?
- Ideal QC test would:
 - Accurately characterize tensile strength
 - Provide a measure of ductility or toughness
 - Can be performed with equipment commonly available at precast concrete plants & local testing laboratories
 - Simple to perform, easy for technicians to learn

POWERING THE NEW ENGINEER TO TRANSFORM THE FUTURE

Engineering School or Sustainable Infrastructure & Environment

Double Punch Test

UF



- 6 in. x 6 in. cylindrical specimen
- Specimen is loaded axially through 2 central punches of 1.5 in. diameter.
- Load is applied at displacement-controlled rate

Choumanidis, D., E. Badogiannis, P. Nomikos, and A. Sofianos. (2017). Barcelona test for the evaluation of the mechanical properties of single sand hybrid FRC, exposed to elevated temperature. *Construction and Building Materials*, *138*. 296-305.

POWERING THE NEW ENGINEER TO TRANSFORM THE FUTURE

Engineering School or Sustainable Infrastructure & Environment

Double Punch Test

UF





Choumanidis, D., E. Badogiannis, P. Nomikos, and A. Sofianos. (2017). Barcelona test for the evaluation of the mechanical properties of single sand hybrid FRC, exposed to elevated temperature. *Construction and Building Materials*, *138*. 296-305.

UF

Engineering School or Sustainable Infrastructure & Environment

Barcelona Testing at UF





Engineering School or Sustainable Infrastructure & Environment

Research Questions

- Can this test be simplified to be performed in a simple compression machine for QC purposes?
- What parameters of the test method must be controlled in the specification?
 - Finishing, casting, punch alignment, load rate
- Do the simplified double punch measured parameters correlate with those of the direct tension test and ASTM C1609, giving confidence that it can be used as a QC index test?

Engineering School or Sustainable Infrastructure & Environment

Ruggedness test design (ASTM E1169)

- Casting method
 - Filled with a scoop (slow filling)
 - Filled with a bucket (fast filling)
- Surface

UF

- Ground with cylinder grinder
- Not ground
- Loading Rates
 - Fast: 700-800 lb/second
 - Slow: 200-300 lb/second
- Punch centering
 - Centered
 - Top punch 5mm off-center



Engineering School or Sustainable Infrastructure & Environment

Results investigated

Max stress

UF

- Toughness
- Displacement location at which peak load occurs





UF

Engineering School or Sustainable Infrastructure & Environment

Significant factors (percent confidence intervals for two factor T test)

	Max stress	Toughness	displacement at peak load
scoop vs. bucket	99.99	100.00	96.72
surface grinding	53.60	56.68	99.47
load rate	1.79	32.91	14.30
centering	67.56	56.61	44.07

95% confidence chosen as threshold for significance

Engineering School or Sustainable Infrastructure & Environment

Results - Simplifying for Dial Gauge

- Continuous axial displacement data was taken with string potentiometers
- Discrete data points at different displacement intervals were selected from continuous measurements to simulated manual recording of strength at these displacement values



POWERING THE NEW ENGINEER TO TRANSFORM THE FUTURE

Engineering School or Sustainable Infrastructure & Environment

Toughness results

Data point displacement interval	Maximum toughness deviation from continuous data
0.050 in.	4%
0.025 in.	1.5%
0.010 in.	2%

UF

Engineering School or Sustainable Infrastructure & Environment

Simplified Setup with Dial Gauge

Axial displacement measurements used instead of circumferential

A dial gage or other simple displacement device can be used.



Templates to align punches

Engineering School or Sustainable Infrastructure & Environment

Double Punch Response to Fiber Percentage

Both fiber types were 13mm long. Straight fibers had diameter of 0.2 mm, twisted had diameter of 0.5mm

POWERING THE NEW ENGINEER TO TRANSFORM THE FUTURE

Engineering School or Sustainable Infrastructure & Environment

Simplified Double Punch Test Compared to Direct Tension Test and ASTM C1609

UF

Engineering School or Sustainable Infrastructure & Environment

Test Method Comparison

Engineering School or Sustainable Infrastructure & Environment

Flexure vs Double Punch

• Double Punch Test

POWERING THE NEW ENGINEER TO TRANSFORM THE FUTURE

Engineering School or Sustainable Infrastructure & Environment

Toughness: Direct Tension vs. ASTM C1609

POWERING THE NEW ENGINEER TO TRANSFORM THE FUTURE

Engineering School or Sustainable Infrastructure & Environment

Relation to Direct Tension Ductility Parameters

Engineering School or Sustainable Infrastructure & Environment

Tensile Testing Summary

- QC Tensile test method MUST have a measure of toughness/ ductility
- Ideal QC test would:

UF

- Accurately characterize tensile strength
- Provide a measure of ductility or toughness
- Can be performed with equipment commonly available
- Simple to perform, easy for technicians to learn
- Round robin study is recommended to implement this test
- Recommendation: Qualify mixtures with direct tension test or ASTM C1609, use new simplified double punch test as QC test at the plant

Engineering School or Sustainable Infrastructure & Environment

Acknowledgements

UF

• FDOT for providing funding for this work. Dale DeFord and Steve Nolan for serving as project monitors.

Ultra-High Performance Concrete and Innovative Concrete Materials for Prestressed **Concrete Girder Repair** Royce Floyd, Ph.D., P.E., S.E. Jeffery S. Volz, S.E, P.E., Ph.D Mujtaba Ahmadi **Michael Mesigh**

Motivation

Bridge Joint Deterioration

Photo curtesy of Walt Peters

http://www.toledoblade.com/local/2011/07/08/Defective-bridge-expansion-joint-causes-I-75-delays.html

alla

allin

1 atthe

2

Corrosion and Spalling of Simply Supported Girders

- në në në në në n

allh

Hatto Hatto

Motivation

Cracking of Continuity Connection Blocks

4 alle

allo 4 allo

Photo curtesy of Walt Peters

UHPC

- General Definition
 - Compressive strength of 18 30 ksi
 - Post-cracking strength of 700 900 psi
- High flowability
- Very low to negligible permeability
- High freeze-thaw resistance
- Durability

UHPC Repair Applications

Expansion Joint Headers

Link Slabs

(Graybeal 2014)

alla

alla

Latte

6

UHPC Repair Applications

Steel girder ends

Concrete girder ends

(Shafei et al. 2020)

<u>Lierenerenerenenen</u>en

allb

allh

(Zmetra 2015)

FR-SCC

- Fiber reinforced self-consolidating concrete
- Flowable and easy to cast
- Good for complex geometry and congested reinforcement
- Fiber reinforcement for restrained shrinkage
- Expansive agent for reduced shrinkage

FR-SCC Repair Applications

• Retaining wall

TERENERE

attle

allh

9

Jarry/Querbes Underpass, Montreal (Khayat et al. 2005)

FR-SCC Repair Applications

• Bridge Pier

Ozyildirim 2013

enenenenenenen

alla

4 alles 4 alles

10

FR-SCC Repair Applications

- Bridge Girder
 - Restored 80% of capacity

atth

alla

allh

11

MALP Concrete

- Magnesium-alumina-aggregate dry powder
- Mono-aluminum-liquid phosphate activator
- Rapid setting and rapid strength gain
- Chemically bonds with base concrete
- Acidic environment reduces halo effect
- Used successfully by other states (Washington, Oregon, North Carolina, Florida, Kentucky, California, New York)

Objectives

- Examine UHPC, FR-SCC, and MALP as repair material
 - Girder end region with shear damage
 - Girder end region with corrosion damage
 - Continuity connection
- Examine effectiveness of UHPC as continuity connection replacement

Girder Design

Cross-Section

Elevation

allba

allh

allh

14

Girder Construction

Girder Construction

16

Repair Materials

- FR-SCC developed by previous research (Wirkman 2016)
- Non-proprietary UHPC developed at OU (Looney et al. 2019)
- MALP was proprietary product Phoscrete

FR-SCC

Material	Quantity (lb/yd ³)
Portland cement (Type I) (lb/yd ³)	412.5
Fly Ash	225
Type K Cement (Komponent)	112.5
Coarse Aggregate (3/8 in. River Rock)	1276
Fine Aggregate	1441
Water	230
Polypropylene Fibers	7.70
Air Entrainer (Master Builders AE-90)	0.54
High Range Water Reducer (Glenium 7920)	4.02
Citric Acid	0.41

UHPC

Material	Quantity
Type I Cement (lb/yd ³)	1180
GGBFS (lb/yd³)	590
Silica Fume (lb/yd³)	197
Steel Fibers (lb/yd³)	265
Fine Masonry Sand (lb/yd ³)	1966
Water (lb/yd³)	393
Glenium 7920 (oz/cwt)	18

17

• Initial test to induce bond-shear failure

18

alla

allh

- Encapsulate end with UHPC, FR-SCC, or MALP
- Concrete screw anchors as shear studs
 - Designed using shear friction

UHPC FR-SCC and MALP

• Completed repairs

MALP

nenenenenen

allita

allh

• Post-repair load tests

UHPC

FR-SCC

MALP

Load-deflection comparison

• Load-deflection for all repaired specimens

allh

• Maximum load comparison

enerenenenenenen erk

alla

alla

alla

Five Spans, three continuous

alliba

25

In-service condition

Pre-repair load test

alla

4 alle

27

Joint demolition and instrumentation

4 allo 4 allo

Joint construction

inenenenenenenenen

alla

4 allo 4 allo

Condition after 1 year

Hann Hann

allh

Post-repair load test

		Load Stage 1	Load Stage 2	Load Stage 3	Load Stage 4	Load Stage 5	Load Stage 6			
0.00									-	
-50.00	1			11						
icrostrain		¥					h 1			
≥ -150.00				1 1		N			• Exterior Joint • Center Joint	
-200.00			1							
-250.00	ł.									
	0	50	00	1000		1500 Time (s)	2000	2500	3000

alle

allh

alle

Load Stage	Measured Before Repair	Calculated for Simple Span	Measured After Repair	Calculated for Continuous Spans
1	-1	-2	-2	-1.5
2	-2	NA	-1	-1.0
3	0	NA	0	0.3
4	0	NA	0	-0.2
5	-1	NA	1	0.5
6	-4	-4	-3	-3.1

Conclusions

- All three repair materials provided increased capacity when used to encapsulate shear damaged end region
- UHPC provided the greatest increase in capacity, even with a smaller thickness
- Repaired specimens exhibited significantly less cracking which could lead to improved longevity
- UHPC was successfully used to replace existing precast concrete girder continuity connections and appears to be functioning as expected

Future Work

- Examine repair of concrete loss below the prestressing strands
- Examine effects of creep, shrinkage, and temperature on the joint when prestressed girders are connected shortly after prestress
- Develop design guidance for UHPC continuity connections

better together

Thank you! rfloyd@ou.edu

-The-

UNIVERSITY

OKLAHOMA

NORCHEM

alle

34

References

- Graybeal, B. (2014) Design and Construction of Field-Cast UHPC Connections, FHWA-HRT-14-084, Federal Highway Administration, McLean, VA.
- Graybeal, B.A. (2014). Splice Length of Prestressing Strand in Field-Cast Ultra-High Performance Concrete Connections, FHWA-HRT-14-041, Federal Highway Administration, Department of Transportation, McLean, VA.
- Khayat, K., Petrov, N., Assaad, J., Morin, R., and Thibault, M. (2005) "Performance of SCC Used in Repair of Retaining Wall Elements." Proceedings, 2nd North American Conf. on the Design and Use of Self-Consolidating Concrete, Ed. Shah, S., Chicago, IL, November, 9 p.
- Looney, T., McDaniel, A., Volz, J., and Floyd, R. (2019) "Development and Characterization of Ultra-High Performance Concrete with Slag Cement for Use as Bridge Joint Material", British Journal of Civil and Architecture Engineering, 1(2): 1-14.
- Maya, L., & Graybeal, B. (2017). Experimental study of strand splice connections in UHPC for continuous precast prestressed concrete bridges. Engineering Structures, 133, 81-90. doi:10.1016/j.engstruct.2016.12.018.
- Miller, R. (2004). Connection of simple-span precast concrete girders for continuity (Report (National Cooperative Highway Research Program); 519). Washington, D.C.: Transportation Research Board.
- Oesterle, R., Glikin, J. D., & Larson, S. C. (1989). Design of precast, prestressed bridge girders made continuous. (Report (National Cooperative Highway Research Program); 322). Washington, D.C.: Transportation Research Board,
- Ozyildirim, C. (2013). "Use of SCC for the Repair of Bridge Substructures." Presentation, ACI 2013 Spring Convention.
- Shafei, B., Phares, B., and Shi, W. (2020). "Beam End Repair for Prestressed Concrete Beams," IHRB Project TR-715, Iowa Department of Transportation, Ames, IA.
- Wirkman, C. (2016). "Performance of Fiber-Reinforced Self-Consolidating Concrete for Repair of Bridge Sub-Structures." MS thesis, University of Oklahoma, Norman, OK
- Yuan, J., and Graybeal, B. (2014). Bond Behavior of Reinforcing Steel in Ultra-High Performance Concrete, FHWA-HRT-14-090, Federal Highway Administration, Department of Transportation, McLean, VA.
- Zmetra, K.M. (2015). "Repair of Corrosion Damaged Steel Bridge Girder Ends by Encasement in Ultra-High Strength Concrete." PhD Dissertation, University of Connecticut, Hartford, CT.

nénénénénénénéné